

## Commdoor Standard Door Configuration

Series	Thickness	Stile	Top Rail	Bottom Rail
175	1-3/4"	2" (50.8mm)	2-1/4" (57.2mm)	3-7/8" (98.4mm)
260	2" insul	2" (50.8mm)	2-1/4" (57.2mm)	3-7/8" (98.4mm)
350	1-3/4"	3-1/2" (89mm)	3-7/8" (98.4mm)	6" (152mm)
360	2" insul	3-1/2" (89mm)	3-7/8" (98.4mm)	6" (152mm)
500	1-3/4"	5" (127mm)	5" (127mm)	6" (152mm)
560	2" insul	5" (127mm)	5" (127mm)	6" (152mm)
200	2"	2-3/8" (60mm)	2-3/8" (60mm)	3-7/8" (98.4mm)

## Order Information

### Standard Door Opening Size:


Single Door 3' x 7' ( 914mm x 2134mm)

Pair Door 6' x 7' (1828mm x 2134mm)


### Door Swing:

When you order doors use the following designation.


LHI



RHI



PAIR-IN



RHO



LHO



PAIR-OUT



### Notes for Door Order:

Custom hardware may require certain stile or rail size.

For non-standard applications contact our customer service department before ordering.

Commdoor will provide glass sizes upon customer's request without guaranty, customers are responsible to double check the sizes.